



Intelligent - Digital - Special

pH MEASUREMENT WITH IDS pH ELECTRODES IN LIFE SCIENCES

New



a xylem brand

pH measurement in Life Sciences ...

... traceable with IDS.

Special pH electrodes extend the range of the IDS series for enhanced applications in Life Sciences and related applications.

pH electrodes with IDS

- Safe measurements by signal processing in the electrode
- Easy exchange of electrodes thanks to calibration data stored in the sensor
- Best GLP support due to automatic documentation of all relevant data
- Exact sensor rating guaranteed by OQS



More IDS electrodes as well as more information on IDS please visit our web site: www.wtw.de/en/ids
(For convenience use our QR code).





SenTix® 945

Fast and universal, a perfect gel electrode for the laboratory

- Three junctions for fast and precise responding
- Gel filling guarantees low maintenance during lifetime
- Smooth glass shaft allows easy cleaning

SenTix® Micro 900

A slender solution for small measurements

- Extra-long, thin shaft supports measurement in small vessels or sample volumes
- Platinum wire junction for fast and stable measurements
- Built-in temperature provides for accurate readings

SenTix® Sp-T 900

No resist against a sharp spear

- Spear type membrane facilitates measurement in semi-solid samples
- Hole junction and polymer electrolyte - Insensitive against pollution and easy to clean
- Built-in temperature provides for accurate readings

SenTix® HW-T 900

Extraordinary samples require outstanding pH electrodes

- Adjustable split ring junction enables measurement in most difficult samples
- Large electrolyte reservoir for reduced maintenance
- Built-in temperature supports accurate readings

**For all digital multi-parameter instruments MultiLine® IDS, inoLab® Multi IDS and pH 3310 IDS.*

Technical Data

Modell	SenTix® 945	SenTix® Micro 900	SenTix® Sp-T 900	SenTix® HW-T 900
Order number	103743	103751	103752	103753
Measuring range	pH: 0.000 ... 14.000 ± 0.002		pH: 2.000 ... 13.000 ± 0.002	pH: 0.000 ... 14.000 ± 0.002
Temperature range	0 ... 80 °C	0 ... 100 °C	0 ... 80 °C	0 ... 60 °C
Reference electrolyte	Gel	KCl 3 mol/l	Polymer	KCl 3 mol/l
Membrane shape	Spherical	Cylindrical	Spear type	Cylindrical
Diaphragm	3 x Ceramic	Platinum wire	Hole	Split ring
Shaft material	Glass		Plastic	Glass
Shaft length	120 mm	70/130 mm	65/25 mm	170 mm
Shaft diameter	12 mm	12/5 mm	15/5 mm	12 mm
Temperature sensor	NTC 30 kOhm			
Connection cable	1.5 m with digital plug			
Stored calibration records	10			
	Accuracy refers to integrated electronics			

What can Xylem do for you?

We're 12,500 people unified in a common purpose: creating innovative solutions to meet our world's water needs. Developing new technologies that will improve the way water is used, conserved, and re-used in the future is central to our work. We move, treat, analyze, and return water to the environment, and we help people use water efficiently, in their homes, buildings, factories and farms. In more than 150 countries, we have strong, long-standing relationships with customers who know us for our powerful combination of leading product brands and applications expertise, backed by a legacy of innovation.

For more information on how Xylem can help you, go to www.xylem.com



WTW Wissenschaftlich-Technische Werkstätten GmbH

Dr.-Karl-Slevogt-Straße 1
D-82362 Weilheim
Germany

Phone: +49 881 183-0
Fax: +49 881 183-420
E-Mail: Info.WTW@Xylem.com
Internet: www.WTW.com

Quotations and Orders
Phone: +49 881 183-324
Fax: +49 881 183-411
E-Mail: Order.WTW@Xylem.com

Technical Information
Phone: +49 881 183-321
Fax: +49 881 183-425
E-Mail: TechInfo.WTW@Xylem.com

Repair Service
Phone: +49 881 183-325
Fax: +49 881 183-414
E-Mail: Service.WTW@Xylem.com